

# *Development of a speed-based surrogate roundabout safety measure*



**Ondřej Gogolín, Jiří Ambros**  
CDV – Transport Research Centre



**Radosław Bąk, Mariusz Kieć**  
Cracow University of Technology



# *Contents*

## **Introduction**

- Roundabout types
- Safety problems

## **The study**

- Data collection on turbo-roundabouts
- Surrogate measures (drivers behaviour, speed)

## **Results**

- Speed-based surrogate roundabout safety measure
- Conclusions

# *Roundabout types*

- Single-lane
- Multi-lane
- Turbo-roundabouts with dividers
- Turbo-roundabouts without dividers
- Various shape of roundabouts (eight)



# How to assess road safety?

- Low occurrence of accidents
- Variables at accident prediction models (traffic exposure, variables reflecting geometric features, and speed features)
- Accident prediction models based on speed:

$$Acc = e^{-16.61} \cdot Q_e^{0.47} \cdot Q_c^{0.26} \cdot S_C^{2.13} \text{ [Turner et al., 2009]}$$

$$Acc = e^{-12.80} \cdot Q_e^{0.81} \cdot e^{0.34 \cdot IAS} \text{ [Persaud et al., 2011]}$$

where:

$Acc$  = annual number of crashes

$Q_e$  = entering flow

$Q_c$  = circulating flow

$S_C$  = free-flow circulating speed

$IAS$  = inside average speed

- Speed through roundabouts = f (deflections, radii, geometric features)
- How to assess geometrical parameters for turbo-roundabouts?

# *Turbo-roundabouts*



- without dividers (trajectory changes are possible)



- with dividers (no trajectory changes)




# Surrogate measures based on driver behaviour







[Chodur and Bąk, 2016]



# Data collection on 15 turbo-roundabouts



# Speed results (1): turbo-roundabouts with dividers



# Speed results (2): turbo-roundabouts without dividers



# *Speed-based surrogate roundabout safety measure*

- Section speed

$$S_{en} = 5,54 + 0,485 \cdot S_{app} + 0,432 \cdot R_{en} \quad R^2 = 0,74 \quad (R_{min} = 12\text{m}, R_{max} = 32\text{m})$$

$$S_{cir} = 22,2 + 0,358 \cdot R_{cir} \quad R^2 = 0,36 \quad (R_{min} = 11\text{m}, R_{max} = 34\text{m})$$

$$S_{ex} = 27,28 + 0,384 \cdot R_{ex} \quad R^2 = 0,24 \quad (R_{min} = 12\text{m}, R_{max} = 30\text{m})$$

- Turbo-roundabouts with dividers

$$IAS_d \text{ – inside average speed [km/h]} \quad (IAS_{min} = 25 \text{ km/h}, IAS_{max} = 42 \text{ km/h})$$

$$IAS_d = -6,87 + 0,334 \cdot S_{en} + 0,394 \cdot S_{cir} + 0,482 \cdot S_{ex} \quad R^2 = 0,98$$

- Turbo-roundabouts without dividers

$$IAS_{nd} \text{ – inside average speed with improper driving [km/h]}$$

$$IAS_{nd} = IAS_d + 3,66 + 0,021 \cdot P_{impdrv} \quad R^2 = 0,81$$

$$P_{impdrv} \text{ – percent of improper driving [\%]} \quad (\text{min} = 15\%, \text{max} = 40\%)$$

# *Conclusions*

- The method allows to evaluate the relative changes in road safety based on observed or calculated speed.
- The use of observed speed, as a surrogate safety measure, allowed to estimate road safety on turbo roundabouts with and without dividers, including driver behaviour.
- Estimation of speed could be improved by using floating car data (speed profiles and trajectories).
- It will be necessary to develop and validate accident prediction models.

*Thank you for your attention*



**Ondřej Gogolín, Jiří Ambros**  
CDV – Transport Research Centre



**Radosław Bąk, Mariusz Kieć**  
Cracow University of Technology

